

RE610-LF

- Eurocard for grids 1.00, 2.00 and 2.54 mm
- Epoxy glass hard fabric FR4 1.50 mm
- Double-sided 35 µm Cu
- Plated-through (PTH)
- Hot Air Leveling (HAL lead free)
- Two raster fields with 7 x 37 soldering pads each (1.70 x 1.70 mm) in raster 2.54 mm (bore Ø 1.10 mm)
- One raster field with 37 x 94 soldering pads (0.70 x 0.70 mm) in raster 1.00 mm (bore Ø 0.30 mm)
- 37 three hole pads in raster 2.54 mm, which are transferred to a raster 1.00 mm
- One raster field with 15 x 47 soldering pads (1.70 x 1.70 mm) in raster 2.00 mm (bore Ø 1.10 mm)
- 37 three hole pads in raster 2.54 mm, which are transferred to a raster 2.00 mm
- Pre-scored predetermined breaking point

- Size 100 x 160 mm

Roth Elektronik GmbH
Industriestr. 4
65594 Runkel-Steeden

Phone: +49 (0)261 134978 - 08

E-Mail: info@roth-elektronik.com

Managing Director Mike Teschke
Register Limbrug HRB 7172
VAT ID no. DE1481222609

Hamburger Volksbank
IBAN DE30 2019 0003 0032 3184 05
BIC GENODEF1HH2